





10,5^{kW} - 15,9^{kW}



HIGH PRESSURE WASHER

Stainless-steel AISI 304 with interchangeable heating elements		
Stainless-steel AISI 304 BA		
V - Hz	√- Hz 3~ 400 - 50/60	
kW/h	9,0	14,4
kW/h	10,5	15,9
I	5	
bar	da 1 a 150	
l/min	2	4
° C	da 20 a 90	
	kW/h kW/h I bar I/min	with interchangeable Stainless-steel V - Hz 3~ 400 - kW/h 9,0 kW/h 10,5 I 5 bar da 1 a I/min 2

VARIOUS

Weight	Kg	57	
Cable	m	8	
Dimensions (generator)	cm	H.99 x L.66 x W. 40,8	
Dimensions (pallet)	cm	53 x 40 x 52	
Pallet/unit	pz	8	



Technical features



Water mains



Water temperature regulation



Water pressure regulation



Contro



Boiler maintenance signal

Hot/cold high-pressure washer with stainless-steel body and boiler:

- The water temperature can be set from 20°C to 90°C.
- The water pressure can be set from 1 to 150bar.
- The ergonomic structure, the fully electric operation and the compact size allows its to usage in any environment.
- · All steam cleaner functions can be managed on the electronic control panel.
- Equipped with hose holder, cable holder, lance holder and front 360° swivel wheels.



ACCESSORIES





APPLICATIONS



