Steam cleaner with stainless-steel body and stainless-steel boiler, designed for professional use and able to deliver dry saturated steam at 165°C - 174°C.

Available in various models.

The ergonomic structure, the fully electric operation and compact size allows to usage

All steam cleaner functions can be managed on the electronic control panel.



ENG

Steam cleaner



Body material

Stainless steel AISI 304 BA

Body material

Stainless steel AISI 304

Power supply

1~ 230 V - 50/60 Hz

2,45 kW/h

Boiler output

2,4 kW/h

1,5 L

3 ^L

Operating pressure

8 bar mod. DET - WATER - 24/7 / 6 bar mod. BASE

Water tank

(only on mod. DET - WATER - 24/7)

3 L

Detergent tank

64 g/min 3,8 Kg/h

Steam temperature

174°C mod. DET - WATER - 24/7 / 165°C mod. BASE

Cable

5 m

Weight

14 Kg

33 x 28 x 42 cm



Scan me!



Models

		DET	WATER	24/7	BASE
8	UNLIMITED STEAM AUTONOMY	•	•	•	-
A	AUTOMATIC WATER REFILLING	•	•	•	-
	MANUAL BOILER REFILLING	-	-	-	•
	DETERGENT TANK	•	-	-	-
•	WATER TANK	•	•	•	-
	DETERGENT INJECTION	•	-	-	-
	OVERHEATED WATER INJECTION	-	•	-	-
888B ••••jim	CONTROL PANEL	•	•	•	•
***	BOILER CLEANING SIGNAL	•	•	•	•

EVO 304 models

FEATURES



Optional

Trolley ARENA PLUS

Water tank - 3 l

only on mod. DET - WATER - 24/7



Detergent tank - 1 l only on mod. DET





Cable holder



System ON







Electric plug SHUKO 5m

Control panel

CONTROL PANEL

- Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- **Buttons and indicators for the** complete control of the parameters of the steam cleaner



Optional accessories

Evo 304 can be used with the following accessories:







STEAM MOP 6 bar Steam accessories





L. 220mm



L. 220mm



Mop L. 220mm

Cotton/polyester cloth L. 220mm




APPLICATIONS





HO.RE.CA







HOUSEHOLD











HEALTH CARE

