Steam Tech

Steam cleaner with polyethylene body and stainless-steel boiler, designed for professional use and able to delivery dry saturated steam at 165 - 183°C.

Equipped with a wet&dry vacuum cleaner with float and a detergent injection system. The sturdy structure, the fully electric operation and compact size allows to usage in any environment.



ENG

Steam cleaner



Body material

PE - Varnished steel

Boiler material

Stainless steel AISI 304

Boiler volume

7 L

Water: 15 L Det: 15 L

3,75 - 8,5 - 12,1 - 15,6 kw/h

3,6 - 7,2 - 10,8 - 14,4 kW/h

Steam production

97 - 194 - 291 - 388 g/min 5,9 - 11,6 - 17,5 - 23 Kg/h

Power supply

1~ 230 V - 50/60 Hz | 3~ 400 V - 50/60 Hz

Steam temperature

6 bar: **165** °C 10 bar: **183°**C

Detergent temperature

90° C - 160°C

Power cord 8 m

Weight 56 Kg

86x54x100 cm

Vacuum cleaner



Power output

1,2 kW/h

14 L

Air flow 200 m3/h Depression 2200 mm



Scan me!







UNLIMITED STFAM AUTONOMY



WATER TANK



DETERGENT TANK





AUTOMATIC DETERGENT WATER INJECTION REFILLING



OVERHEATED WATER INJECTION



CONTROL PANEL



VACUUM CLEANER WITH FLOAT



MADE IN

BOILER CLEANING SIGNAL



Optional accessories

Steam Tech can be used with the following accessories:



Geyser 1 10bar - Steam



Radames 10bar - Steam & vacuum



July 10bar - Steam



Kit Car Wash 6bar / 10bar - Steam & vacuum



Star 6bar - Steam & vacuum



RADAMES 6bar - Steam & vacuum



July 6bar - Steam



APPLICATIONS





CAR WASH







INDUSTRY







TRANSPORT INDUSTRY

MECHANICAL **INDUSTRY**









