designed for professional use and able to deliver dry saturated steam at 165°C or 174°C. Equipped with an overheated water injection system (available only for the 8-bar model). The ergonomic structure, the fully electric operation and compact size allows to usage in any environment.

All steam cleaner functions can be managed on the electronic control panel.



ENG

Steam cleaner



Upper: ABS VO

Lower: Varnished steel

Body material

Stainless steel AISI 304

Power supply

1~ 230 V - 50/60 Hz

2,45 kW/h

2,4 kW/h

1,5 L

Operating pressure

6 bar - 8 bar

Water tank

3 L

64 g/min 3,8 Kg/h

Steam temperature

165 ° - 174 ° c

5 m

Weight

14 Kg

32 x 32 x 41 cm







FEATURES







WATER TANK



AUTOMATIC WATER REFILLING



OVERHEATED WATER INJECTION



CONTROL PANEL



BOILER CLEANING SIGNAL



SHUKO 5m

CONTROL PANEL

- · Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- **Buttons and indicators for the** complete control of the parameters of the steam cleaner



Optional accessories

Gal can be used with the following accessories:







STEAM MOP 6 bar Steam accessories






APPLICAZIONI





HO.RE.CA







DOMESTICO

SANITÀ







