CAR WASH RANGE

**Car Hygiene Plus** 

Self-service cabinet with stainless-steel body and boiler able to deliver dry saturated steam at 165°C. Specifically designed for the car wash sector. Equipped with an internal PLC and timer, which enables to set the duration of its steam/vacuum functions.

Multiple versions are available according to every need.



CAR HYGIENE PLUS

SELF-SERVICE

USER INSTRUCTION

WARNINGS

THINK ABOUT YOUR HEALTH!

TECN I/AP

**ENG** 



Stainless steel AISI 304 BA

### **Stainless steel AISI 304**

**Power supply** 

### 3~ N 400 <sup>V</sup> - 50/60 <sup>Hz</sup>

Maximum output	Boiler output
<b>6,7</b> <sup>kW/h</sup>	<b>3,6</b> <sup>kW/h</sup>
Operating pressure	Boiler volume
<b>6 <sup>bar</sup></b>	<b>7</b> <sup>L</sup>

### 0.16 kW/h

Tanks

215 Kg

Vacuum cleaner

Power output 3 kW/h

Air flow

320 m3/h

Water: 20<sup>L</sup> | Det: 6<sup>L</sup>

5,9 Kg/h

**97** g/min

Steam temperature

Detergent temperature **90° C - 160°**<sup>c</sup>

**165** °c

Weight

30<sup>L</sup>

Depression

3200 mm

164x85x85 cm



WATER

TANK



TIZES the inte

REMOVES stains from seats and upholstery

EMOVES bad smells

O SA

0



AUTOMATIC WATER REFILLING



INDUCTION TURBINE

BOILER CLEANING SIGNAL



UNLIMITED

STEAM AUTONOMY

DETERGENT

INJECTION

**FEATURES** 





DETERGENT

TANK





Scan me!

# **ACCESSORIES and FUNCTIONS**

CAR HYGIENE PLUS

## **POSSIBLE CONFIGURATIONS**

During the ordering process, it is possibile to personalize the duration of every function.







\*Possibility to customize the payment acceptor for the local currency

### **APPLICATIONS**



