



Steam Box Pro

4,8^{kW} - 8,4^{kW} - 11,1^{kW} - 15,6^{kW}

STEAM CLEANER

Boiler	Stainless-steel AISI 304 with interchangeable heating elements				
Body	Stainless-steel AISI 304 BA				
Power supply	V - Hz	V - Hz 3~ 400 - 50/60			
Boiler output	kW/h	3,6	7,2	10	14,4
Maximum output	kW/h	4,8	8,4	11,1	15,6
Boiler volume	I	7			
Operating pressure	bar	10			
Water tank	I	14			
Detergent tank	I	14			
Steam production	g/min	97	194	272	388
	Kg/h	5,9	11,6	16,3	23
Steam temperature	° C		183		
Detergent temperature	° C	90 - 160			

VACUUM CLEANER

Power output	kW/h	1	
Drum capacity	1	7,5 14	
Air flow	m3/h	200	
Depression	mm	2200	

VARIOUS		
Weight	Kg	82
Cable	m	8
Dimensions (generator)	cm	H.120,4 x L.53 x W. 82,5
Dimensions (pallet)	cm	115x65x125
Pallet/unit	pz	1



Technical features























Operating pressure 10 bar

Water

Detergent tank

Control panel


Steam cleaner with stainless-steel body and boiler, designed for industrial use and able to deliver dry saturated steam at 183° C:

- Equipped with a wet/dry vacuum cleaner with an induction turbine.
- · A sturdy structure, a fully electric operation and the compact size allows its a usage in any environment, both outdoors (watertight protection IPX5) and indoors (e.g. in production lines).
- · All steam cleaner functions can be managed on the electronic control panel.
- Equipped with accessories basket, hose/cable holder and front 360° swivel wheels with safety brakes.





Features



Vacuum inlet



Detergent tank 14 liters



Hose holder



Detergent tank level indicator



Steam outlet 10bar - 12P



Optional accessories

Steam Box Pro can be used with the following accessories:



Steam/vacuum accessories

GEYSER 1 10bar RADAMES 10bar











Floor tool L. 375mm



Squeegee/brush insert L.375mm - 2pcs




insert L.375mm

brush Ø60mm



JULY 10 bar Steam accessories



CONTROL PANEL

- Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- **Buttons and indicators for the complete** control of the parameters of the steam cleaner



• IEC309/16A Mod. 3,6 - 7,2 - 10 kW IEC309/32A Mod. 14,4 kW

Version without vacuum cleaner

Power regulation / On - Off switch

Vacuum coupling

Water tank 14 liters

Accessory baskets,

extension tube holder &

water tank level indicator

Water mains connection

Electric plugs - 8m:





brushes Ø28mm

APPLICATIONS





INDUSTRY













TRANSPORT INDUSTRY









