

STEAM





Steam Turbo

10,8^{kw} - 17,4^{kw} - 21^{kw} - 21,6^{kw} - 31,8^{kw} - 39^{kw}

STEAM CLEANER

Boiler	Stainless-steel AISI 304 with interchangeable heating elements						
Body	Stainless-steel AISI 304 BA						
Power supply	V - Hz 3~ 400 - 50 (60Hz on request)						
Boiler output	kW/h	10,8	14,4	18	21,6	28,8	36
Maximum output	kW/h	10,8	17,4	21	21,6	31,8	39
Boiler volume	13						
Operating pressure	bar from 1 to 10						
Water tank	14						
Detergent tank	I	14					
Steam production	g/min	291	388	485	582	776	970
	Kg/h	17,5	23	29,1	35	46,5	58
Steam temperature	° C	165 - 183					
Detergent temperature	° C	90 - 160					

VACUUM CLEANER

Power output	kW/h	3	
Drum capacity	I	14 43	
Air flow	m3/h	320	
Depression	mm	3200	

VARIOUS

VARIOUS		
Weight	Kg	151
Cable	m	8
Dimensions (generator)	cm	H.166 x L.69 x W. 95,5 drum 43I
Dimensions (pallet)	cm	120x80x165
Pallet/unit	pz	1



Technical features

























Operating pressure

Water

Water tank

ter Deterg

gent Au k

Automatic water refilling

Detergeni injection Ove V ini rheated Power vater regulation ection switch Steam pressure regulation

Induction turbine

Control panel Boiler maintenance signal

Steam cleaner with stainless-steel body and boiler, designed for industrial use and able to deliver dry saturated steam at 183° C:

- Equipped with a wet/dry vacuum cleaner with an induction turbine and drainage pipe.
- A sturdy structure, a fully electric operation and the compact size allows its a usage in any environment, both outdoors (watertight protection IPX5) and indoors (e.g. in production lines).
- · All steam cleaner functions can be managed on the electronic control panel.
- Equipped with accessories basket, double hose holder, lance holder, cable holder and front 360° swivel wheels with safety brakes.





Features

Vacuum cleaner with induction turbine and drum capacity of 14 l or 43 l



Detergent tank - 14 liters



- High pressure pump level indicator
- Detergent tank level indicator
- Hose holder & Geyser lance holders



Steam outlet 12P




Optional accessories

Steam Turbo can be used with the following accessories:















Steam/vacuum turbo lance



Brass/stainless steel brushes Ø28mm - Ø60mm







Floor tool L. 375mm

Squeegee/brush insert L.375mm - 2pcs

JULY 10 bar Steam accessories

Steam lance



5m - 8m - 10m - 12m







Triangular brush



Stainless steel/brass brushes Ø28mm







- Display to visualize temperature and pressure levels, working hours and boiler cleaning signal
- Steam flow and pressure regulation
- **Buttons and indicators for the complete** control of the parameters of the steam cleaner



APPLICATIONS





FOOD INDUSTRY













TRANSPORT INDUSTRY









